



GTS SUPER 300 HPE - TECHNICAL SPECIFICATIONS

ENGINE	4-valve 4-stroke single cylinder, electronic injection, catalysed hpe
DISPLACEMENT	278.3 cc
BORE X STROKE	75 mm x 63 mm
MAX POWER AT THE CRANK SHAFT	23.8 HP - at 8,250 rpm
MAX TORQUE	19.17 ft-lb at 5,250 rpm
CONSUMPTION	73.38 mpg
CO2 EMISSIONS COMPLIANCE	74 g/km
FUEL SYSTEM	Electronic Injection
COOLING	Liquid
STARTER	Electric
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and hydraulic shock absorber
REAR SUSPENSION	Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions
FRONT BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
REAR BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
ABS/ASR SYSTEM	ABS/ASR standard
FRONT TIRE	Tubeless 120/70 - 12"
REAR TIRE	Tubeless 130/70 - 12"
LENGTH/WIDTH/WHEELBASE	76.77 / 29.72 / 54.13 in
SEAT HEIGHT	31.1 in
FUEL TANK CAPACITY	2.24 gal
EMISSIONS COMPLIANCE	Euro 4